

# YARRAN

## NATURAL SLATE STACKED STONE

*Product Spec V3*



**InfinitiStone®**  
Your Natural Choice in Stone Cladding

# PRODUCT

---

Our **YARRAN** is a natural slate stone cut into rectangular strips and factory prepared to create wall panels. Being open flat cut around side edges and sawn smooth at back ensures easy, cost efficient, dry stacked stone wall installation. Suits simple, light textural effect stone feature designs.



## Design and Dimensions



Available in 600mm Wide x 150mm High wall panels x 8-15mm thick varying depth.

### Corners

Not available - Form Mitre or Interweave  
joins by installer

### Weight

Approx. 35kg/m<sup>2</sup>

### Packaging

Sold in 0.72m<sup>2</sup>/box flats  
ie 8 pieces per box.

### Colour

Grey, rust, golden brown & brown tones – ratios vary

# INSTALLATION

## Handy Tips

- All substrates must be free from dust and release agents prior to installation
- We recommend cladding onto structurally sound substrates.
- If using pre-mix adhesives such as Mapei Keraflex Maxi S1 or equivalent, ensure to wipe off excess from face of stone immediately with a wet sponge.
- Starting from bottom, work your way up the project wall, row by row, staggering your joins.
- Check levelness every few rows.
- Work with a few boxes at a time for best consistency in colour variation, profile and pattern
- View our Installation Guide for full installation details.

**Cutting:** Use a quality wet tile saw or grinder with a diamond blade or similar. If you do not have one, you can hire one from your local building equipment hire store.

**Joint Finish:** This range is installed via dry stacked method.



## Sealing:

Slate Natural stone are generally porous by nature with high ion content which bleeds out under inclemental weather and therefore sealing with appropriate sealers are recommended. This process limit discolouration and protects from serious common damage from liquids, including: salt attack, freeze-thaw damage, spalling and picture framing and inhibits the growth of mosses and moulds in the pores of the stone.

### Important Note

While reasonable efforts have been made to ensure the contents of this publication are factually correct, InfinitiStone, DIYHQ or DIY International does not accept responsibility for the accuracy or completeness of the contents and shall not be liable for any loss or damage that may occur directly through the use of, or reliance on, the contents of this publication.

**SILICA DUST HAZARD** - When natural stone or rock and other silica containing products are cut, crushed or sanded, dust is released. The very fine portion of the dust that is generated is known as respirable crystalline silica or silica dust. **Ensure to use necessary Personal Protective Equipment when cutting or shaping Natural or manufactured Stone Products.**